Signal Panel

Type: FIM1300

Product ID: 2TKA002136G1

GTIN: 6410070607537

IP20

Could be used as an 3/6 points alarm receiving panel in calling and alarm systems. With 6 LED's. Good marking possibilities. Operating voltage: 12 - 24 V ac/dc. Current consumption/LED: 4 mA ac / 7 mA dc.

Technical specification

Classification

Enclosure class:	IP20

Dimensions

Dimensions:	71x71x35 mm
Weight:	40 g

Thermal conditions

Operating temperature:	5 … 40 °C
Storage temperature:	-40 … 70 °C

Signal products

Operating voltage of signal lamp:	12 - 24 V ac/dc
Current drain of signal lamp:	4 mA ac / 7 mA dc

© ABB 2026
Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

ABB Exchange
+358 10 22 11

Packing

Package:	1/10/100/1200
Unit:	PCS

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002247
Model:	Signalling set
Colour:	White
RAL-number (similar):	9010
Voltage type:	AC/DC
With transformer:	No
Degree of protection (IP):	IP20
Device width:	71 mm
Device height:	71 mm
Device depth:	35 mm

© ABB 2026
Business ID 0763403-0
www.installationmaterials.com

Customer service
puh. +358 10 222 1999
contact.center@fi.abb.com

ABB Exchange
+358 10 22 11