

---

# Table Panel Terminal

---

**Type:** FOT2000

**Product ID:** 2TKA002177G1

**GTIN:** 6410070606134



Terminal for connecting the Table Panel FIP2000. Includes RJ12 type terminal. Operating voltage 15 - 28 V ac.

## Technical specification

### Electrical quantities

Nominal voltage:	24 V
Operating voltage:	15 - 28 V ac

### Classification

Suitable for degree of protection (IP):	IP20
---	------

### Dimensions

Dimensions:	71x71x36 mm
Weight:	47 g

### Thermal conditions

Operating temperature:	5 ... 40 °C
Storage temperature:	-40 ... 70 °C

### Signal products

Load capacity of contact:	1,0 A ac/dc, 42 V ac / 60 V dc, 30 VA / W
---------------------------	---

## Packing

Package:	1/10/100/1200
Unit:	PCS

## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000064
Assembly arrangement:	Other
With light source:	No
With flashlight:	No
With fixed symbol/imprint:	No
With exchangeable symbol:	No
Application as button:	No
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Yes
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	White
RAL-number (similar):	9010
Transparent:	No
Device width:	71 mm
Device height:	36 mm
Device depth:	71 mm
Min. depth of built-in installation box:	21 mm