

Double mounting box

Type: AU17.2

Product ID: 2TKA130026G1

GTIN: 6410011523896



The box AU17.2 has knock-outs for 11 inlets on the side, and 6 on the bottom. It can accommodate a device with a triple inlet. If necessary, the box may be divided in two by using partition plate PMR345. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).

Technical specification

Packing

| | |
|----------|-----|
| Package: | 50 |
| Unit: | PCS |

ETIM Data

| | |
|-------------------------------|--------------------------------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC002601 |
| Mounting method: | Flush mounted (plaster) |
| Shape: | Rectangular |
| Construction type: | Device connection box (round/square) |
| Model: | Double |
| Provided with revolving ring: | No |
| Connectable: | Yes |
| Equipped with: | None |

| | |
|--|------------|
| Length: | 142 mm |
| Width: | 71 mm |
| Depth: | 142 mm |
| Inner depth: | 45 mm |
| For number of electric fittings: | 1 |
| Mounting switching equipment: | Screwing |
| With screws: | Yes |
| Housing feed-through by break-out opening: | No |
| Housing feed-through by seal membrane: | No |
| Housing feed-through by nozzle: | No |
| Housing feed-through by step membrane: | No |
| For tube diameter: | 20/25 mm |
| Pipe locking: | Yes |
| Pipe locking optional: | No |
| Inlet from the rear: | Yes |
| Material: | Plastic |
| Halogen free: | Yes |
| Surface protection: | Untreated |
| Colour: | White |
| Degree of protection (IP): | IP44 |
| Transparent cover: | No |
| Cover attachment: | Snapped on |
| Sealable: | No |
| With screening: | No |
| Air tight: | No |
| Clamp position fixed: | No |
| Luminaire hook mounting: | No |
| Special application: | None |