
Tele outlet

Tele outlet, 22,5mm hole, painted steel

Typ: 2533-866

Produkt ID: 2CKA001724A4270

GTIN: 4011395087244



Center plate with a round 22,5mm dented opening that prevents rotation. Used for fastening different devices. It is suitable for the 85mm cover frames. The manufacture material is a durable high quality plastic. The surface is painted. Cleaning with a mild, standard household detergent. Be careful when cleaning with a powerful dissolvent.



Teknisk specifikation

Klassificering

Suitable for degree of protection (IP):	IP20
---	------

Packning

Förpackning:	1/10/100/2800
--------------	---------------

Enhet:	st
--------	----

ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC000018
-------------	----------

Assembly arrangement:	Control element
-----------------------	-----------------

Utilization:	Other
--------------	-------

Support ring:	Ja
---------------	----

With dust cover:	Nej
With hinged lid:	Nej
Outlet direction:	Straight
Imprintable label:	Without indication field
With imprint:	Nej
Mounting method:	Flush mounted (plaster)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Anti-bacterial treatment:	Nej
Surface protection:	Lacquered
Surface finishing:	Matt
Colour:	Stainless steel
Transparent:	Nej
Type of fastening:	Mounting with screw
Number of modules (module system):	1
With buses/couplings:	Nej
Suitable for number of connectors:	1
With strain relief:	Nej
Shielded buses:	Nej
Shielded housing:	Nej
Luster terminal:	Nej
With lighting:	Nej
Device width:	71 mm
Device height:	71 mm
Device depth:	17.8 mm
Min. depth of built-in installation box:	32 mm