

---

# Electronic Controls

## Busch-Rotary-Dimmer Electronic Controls white

---

**Typ:** 6523 URCGL-916-104

**Produkt ID:** 2CKA006512A0356

**GTIN:** 4011395344095



LED dimmer With rotary control.

Two-way switch and soft-catch.

With N-terminal.

2- or 3-wire connection (neutral conductor not required).

Neutral conductor optionally connectable (recommended for the connection of low loads < 10 W/VA).

Without claws.

Very low installation depth: < 20 mm Without claws.

Optimised for dimming of retrofit LED lamps (LEDi).

For dimmable Retrofit-LEDs (LEDi).

For dimmable Retrofit-LEDs (LEDi) with conventional or electronic transformers.

For incandescent lamps, 230 V tungsten halogen lamps, low-voltage halogen lamps with conventional or electronic transformers and dimmable energy-saving halogen lamps.

Mix operation of LEDi with conventional loads possible.

With manually adjustable operating mode: trailing / leading edge control.

With adjustable minimum/maximum brightness.

Low-noise level by MOSFET transistors.

With electronic short-circuit protection. With electronic overload protection.

With Saga cover plate.

Rated voltage: 230 V~, + 10% / - 10% Rated frequency: 50 Hz/60 Hz

Nominal power (L): 2 - 100 W/VA (leading-edge control)

Nominal power (R, C): 10 - 360 W/VA (trailing-edge control)

Nominal power (LEDi): 2 - 100 W/VA (leading-edge control)

Nominal power (LEDi): 2 - 200 W/VA (trailing-edge control)

# Teknisk specifikation

## Klassificering

Suitable for degree of protection (IP):	IP21
---	------

## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000025
Assembly arrangement:	Basic element with central cover plate
Method of operation:	Turn/push button
App control via Bluetooth:	Nej
Dimming phase cut-on:	Ja
Dimming phase cut-off:	Ja
Serial dimmer:	Nej
Type of load:	Universal and LED Retrofit
Substation input:	Nej
Light value memory:	Ja
Applicable with button:	Nej
Applicable with movement sensor:	Nej
Applicable with presence indicator:	Nej
Applicable with time switch/timer:	Nej
Applicable with transmission button:	Nej
Applicable with infrared button:	Nej
Minimum brightness controllable:	Ja
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Nej
Surface protection:	Untreated
Surface finishing:	Glossy
Colour:	White

RAL-number (similar):	9003
Transparent:	Nej
Impact strength:	IK00
Nominal voltage:	230 V
Max. switching power LED:	360 W
Connection type:	Screwed terminal
Core cross section:	1...2.5 mm <sup>2</sup>
Device width:	71 mm
Device height:	71 mm
Device depth:	45 mm
Min. depth of built-in installation box:	20 mm
Compatible with Apple HomeKit:	Nej
Compatible with Google Assistant:	Nej
Compatible with Amazon Alexa:	Nej
IFTTT support available:	Nej