

Dimmer

With integrated power supply

Typ: 2117/11 U-500

Produkt ID: 2CKA006599A2988

GTIN: 4011395152225



For DALI broadcast service (via central telegram).
For switching and dimming up to 37 DALI- devices like electronic ballasts and transformers with DALI-interface.
With rotary control and ON/OFF push operation.
With electronic short-circuit protection. With electronic overload protection.
Brightness power-on level and background brightness level adjustable, buffered.
With integrated LED illumination for orientation.
Color of orientation light adjustable (18 presets and OFF).
Up to 5 potentiometers are connectable in parallel.
Up to 3 potentiometers are connectable in parallel in active mode.
Not suitable in combination with other DALI-sensors.
DALI-voltage: 15, 5 V=
Rated current: max. 75 mA
Power consumption: < 2, 5 W
Number of DALI-units:
37 in case of one active power-potentiometer
in case of three active power-potentiometer in parallel connection: 111
Active mode: the potentiometer is supporting the necessary control circuit for other DALI-devices.
Passive mode: the potentiometer is suitable as additional operation point.
Max. DALI-cable length: 300 m (1, 5 - 2, 5 mm²).
Without cover plate.
Rated voltage: 230 V~, +10% / -10%
Rated frequency: 50 Hz - 60 Hz
Protection class (Device): IP 20
Temperature range (Device): 0 °C to 35 °C

Teknisk specifikation

Elektriska värden

Nominal voltage:	230 V
------------------	-------

Packning

Förpackning:	1/10
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000534
Mounting method:	Flush mounted (plaster)
Rated current:	0.08 A
Method of operation:	Turn/push button
Substation input:	Ja
Light value memory:	Ja
Min. depth of built-in installation box:	28.5 mm
Device width:	71 mm
Device height:	71 mm
Device depth:	51 mm
Metallic colour:	Nej
Compatible with Apple HomeKit:	Nej
Compatible with Google Assistant:	Nej
Compatible with Amazon Alexa:	Nej
IFTTT support available:	Nej