

Sensor element for movement sensor

Busch-Watchdog® Cover Plate Movement sensor - Saga



Typ: 64761-916-510

Produkt ID: 2CKA006800A3057

GTIN: 4011395316344

Movement detector sensor with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. ./.. Compatible with all free@home flex inserts. Adjusting elements on rear side. Extension of the detection range by means of master/slave combination. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 14 sectors with 56 switching segments. Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable. For relay insert flex, 1gang, 64811 U. For e-contact insert flex, 1gang, 64814 U. For series relay insert flex, 2gang, 64821 U. For LED touch dimmer insert flex, 1gang, 64851 U. For extension insert flex, 64891 U. Mounting height: 22 mm.

Teknisk specifikation

Klassificering

Suitable for degree of protection (IP):	IP20
---	------

Packning

Förpackning:	1/1
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC000138
Model:	Movement sensor
Mounting method:	Flush mounted (plaster)
Constant light control:	Nej
HVAC-control:	Nej
Networkable:	Ja
Suitable for wireless transmission:	Nej
Creep-under protection:	Nej
Max. transmission range sideways:	12 m
Max. transmission range frontally:	12 m
Response value luminosity adjustable:	Ja
Teach-function for response value luminosity:	Nej
Dim function with dimmer basic element:	Nej
Animal zone:	Ja
Staircase monitoring:	Nej
Combination movement sensor/push button switch:	Nej
With orientation lighting:	Nej
Material quality:	Thermoplastic
Halogen free:	Nej
Min. switch-on time:	10 s
Max. duty cycle:	30 min
Switch-off delay self-learning:	Nej
Detection angle horizontal:	0...180 °
Compatible with Apple HomeKit:	Nej
Compatible with Google Assistant:	Nej
Compatible with Amazon Alexa:	Nej
IFTTT support available:	Nej