

# Socket outlet

Socket outlet, Impressivo, Schuko, 1-gang, shuttered, screwless terminals, aluminum



**Typ:** 20EUC-83

**Produkt ID:** 2TKA00000435

**GTIN:** 6438199001456



There are terminals for each contact of the socket outlet. No 2 X-terminals. The terminals are for max 2 rigid wires.

## Teknisk specifikation

### Elektriska värden

Nominal current:	16 A
Nominal voltage:	250 V

### Klassificering

Suitable for degree of protection (IP):	IP21
-----------------------------------------	------

### Packning

Förpackning:	1/10/100/1800
Enhet:	st

### ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Number of active pins (round):	2

With signal lamp:	Nej
Number of units:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Nej
With enhanced contact protection:	Ja
Label space/information surface:	Nej
Colour:	Aluminium
RAL-number (similar):	9006
Metallic colour:	Ja
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	Nej
With loop through function:	Nej
With on/off switch:	Nej
Rotated central insert:	Nej
Frequency:	50 Hz
Device width:	71 mm

# Produktblad

Socket outlet, Impressivo, Schuko, 1-gang, shuttered, screwless terminals, aluminum



---

Device height:	45 mm
Device depth:	71 mm
Min. depth of built-in installation box:	28 mm

---