

Socket outlet

Socket outlet, ProDuct, 2xShuko, white



Typ: AUD10-214

Produkt ID: 2TKA00000809

GTIN: 6438199002019



The socket-outlet is approved for extending a branch circuit with solid and rigid wires. When chaining several AUD10-socket-outlets, the recommended length of intermediate cables is 120 mm. The end piece package AUD30 or AUD31 is required for each socket group. The depth of box is 45 mm.

Teknisk specifikation

Elektriska värden

Nominal current:	16 A
Nominal voltage:	250 V

Klassificering

Suitable for degree of protection (IP):	IP20
---	------

Packning

Förpackning:	10/100
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125

Number of active pins (round):	2
With signal lamp:	Nej
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Nej
With enhanced contact protection:	Ja
Label space/information surface:	Nej
Colour:	White
RAL-number (similar):	9010
Metallic colour:	Nej
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Wall duct
Type of fastening:	Snap mounting (engagement)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Nej
With loop through function:	Nej
With on/off switch:	Nej
Rotated central insert:	Nej
Frequency:	50 Hz

Produktblad

Socket outlet, ProDuct, 2xShuko, white



Device width:	45 mm
Device height:	85 mm
Device depth:	80 mm
