

Socket outlet unit

Socket outlet unit, ProDuct, 6xShuko, white



Typ: AUD13-214

Produkt ID: 2TKA00000821

GTIN: 6438199002132



Ready-to-install 2-gang socket outlet that contains an end package, covers, a junction box with strain-reliefs and a 3 connectors. Approved for 3-phase linking.

Teknisk specifikation

Elektriska värden

Nominal current:	16 A
Nominal voltage:	250 V

Klassificering

Suitable for degree of protection (IP):	IP20
-----------------------------------------	------

Dimensions

Dimensions:	345x85x45 mm
-------------	--------------

Packning

Förpackning:	1/25
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	Nej
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Ja
With enhanced contact protection:	Ja
Label space/information surface:	Nej
Colour:	White
RAL-number (similar):	9010
Metallic colour:	Nej
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Wall duct
Type of fastening:	Snap mounting (engagement)
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Nej
With loop through function:	Nej
With on/off switch:	Nej

Produktblad

Socket outlet unit, ProDuct, 6xShuko, white



Rotated central insert:	Nej
Frequency:	50 Hz
Device width:	45 mm
Device height:	85 mm
Device depth:	350 mm