

---

# DCL lighting outlet for walls

AKK6-81.1 DCL lighting outlet for walls  
Anthracite IP20

---

**Typ:** AKK6-81

**Produkt ID:** 2TKA00000936

**GTIN:** 6438199002361



DCL lighting outlet, wall outlet, 85x85mm, anthracite

## Teknisk specifikation

### Elektriska värden

Nominal current:	6 A
Nominal voltage:	250 V

### Klassificering

Suitable for degree of protection (IP):	IP20
---	------

### Dimensions

Dimensions:	85x85x38 mm
-------------	-------------

### Packning

Förpackning:	10/100
Enhet:	st

### ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC000125
Model:	DCL
With signal lamp:	Nej
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
With hinged lid:	Nej
With enhanced contact protection:	Nej
Label space/information surface:	Nej
Colour:	Anthracite
RAL-number (similar):	7021
Metallic colour:	Nej
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Untreated
Surface finishing:	Glossy
Anti-bacterial treatment:	Nej
With loop through function:	Nej
With on/off switch:	Nej
Rotated central insert:	Nej
Frequency:	50...60 Hz

Impact strength:	IK00
Device width:	39 mm
Device height:	85 mm
Device depth:	85 mm
Min. depth of built-in installation box:	25 mm