

Lighting outlet

DCL lighting outlet, ceiling outlet, surface mounting



Typ: AKK15

Produkt ID: 2TKA00001164

GTIN: 6438199003078



Ceiling rose AKK15 is an earthed, bipolar class 1 ceiling rose. AKK15 crown cover can be mounted directly onto the ceiling or onto the junction box. The group cables, 2,5 mm² (-o-), may be continued. Each ceiling rose can carry a max. 6 A 250 V lighting appliance up to the weight of 15 kilos.

Teknisk specifikation

Elektriska värden

Nominal current:	6 A
Nominal voltage:	250 V

Klassificering

Suitable for degree of protection (IP):	IP20
---	------

Dimensions

Height:	60 mm
---------	-------

Packning

Förpackning:	4/40
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
Model:	DCL
With signal lamp:	Nej
Number of units:	1
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
With hinged lid:	Nej
With enhanced contact protection:	Nej
Label space/information surface:	Nej
Colour:	White
RAL-number (similar):	9010
Metallic colour:	Nej
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Nej



With loop through function:	Nej
With on/off switch:	Nej
Rotated central insert:	Nej
Frequency:	50...60 Hz
Impact strength:	IK00
Device width:	115 mm
Device height:	64 mm
Device depth:	115 mm