

Socket outlet

Socket outlet, Impressivo, Schuko, 2-gang, shuttered, screwless terminals, lath installation, white



Typ: 402EL-84

Produkt ID: 2TKA00002273

GTIN: 6438199003894



There are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals.

Teknisk specifikation

Elektriska värden

| | |
|------------------|-------|
| Nominal current: | 16 A |
| Nominal voltage: | 250 V |

Klassificering

| | |
|-----------------------------------------|------|
| Suitable for degree of protection (IP): | IP21 |
|-----------------------------------------|------|

Packning

| | |
|--------------|------|
| Förpackning: | 1/10 |
| Enhet: | st |

ETIM Data

| | |
|--------------------------------|----------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000125 |
| Number of active pins (round): | 2 |

| | |
|-----------------------------------|---------------------------|
| With signal lamp: | Nej |
| Number of units: | 2 |
| Number of phases: | 1 |
| Imprint/indication: | None |
| Connection type: | Push-in clamp |
| With hinged lid: | Nej |
| With enhanced contact protection: | Ja |
| Label space/information surface: | Nej |
| Colour: | White |
| RAL-number (similar): | 9016 |
| Metallic colour: | Nej |
| Transparent: | Nej |
| Lockable: | Nej |
| Eject-mechanism: | Nej |
| Insulated mounting: | Nej |
| With function lighting: | Nej |
| With orientation lighting: | Nej |
| Over voltage protection: | Nej |
| Fault current protection: | Nej |
| With miniature fuse: | Nej |
| Special power supply: | No special power supply |
| Mounting method: | Surface mounted (plaster) |
| Type of fastening: | Mounting with screw |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Ja |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Anti-bacterial treatment: | Nej |
| With loop through function: | Nej |
| With on/off switch: | Nej |
| Rotated central insert: | Nej |
| Frequency: | 50 Hz |
| Device width: | 100 mm |
| Device height: | 42 mm |

Produktblad

Socket outlet, Impressivo, Schuko, 2-gang, shuttered, screwless terminals, lath installation, white



Device depth:

145 mm