

Renovation 1,5 box

Mounting box for flat socket outlet

Typ: AUS90

Produkt ID: 2TKA00002897

GTIN: 6438199004563



The AUS90 is a front-mounted mounting box for flat socket outlet (for example 302EUJT) with telescope bottom part for board walls of 1 – 3 gypsum boards (thickness of the wall 9 – 39 mm). The height of the box is 54 – 70 mm thanks to the moving bottom part. The installation hole diameter is 73 X 90 mm (box drill AT4). At the side of the bottom part are three inlets for the 16 mm flexi pipe. There is also one inlet for the 16/20 mm and one inlet for the 20 mm flexi pipe.). There are two inlets with strain reliefs on the bottom of the box for installing 8 - 13 mm cables and two inlets for the low voltage cables. The box has four openings, one on each side, through which conductors can also be conveyed from one box to another. At the top of the box there are two fixing places for screws to install it to the log wall. At the bottom there are marking holes for drilling the installation holes overlapping each other. The protection class is IP3X. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).

Teknisk specifikation

Packning

Förpackning:	50
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC002601
Mounting method:	Flush mounted (plaster)
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	One and a half
Provided with revolving ring:	Nej
Connectable:	Ja
Equipped with:	None
Length:	88 mm
Width:	73 mm
Depth:	88 mm
Inner depth:	52 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Ja
Housing feed-through by break-out opening:	Ja
Housing feed-through by seal membrane:	Nej
Housing feed-through by nozzle:	Nej
Housing feed-through by step membrane:	Nej
For tube diameter:	16 mm
Suitable for cable diameter:	8 mm
Pipe locking:	Ja
Pipe locking optional:	Nej
Inlet from the rear:	Nej
Material:	Plastic
Halogen free:	Ja
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP3X
Transparent cover:	Nej
Sealable:	Nej
With screening:	Nej
Air tight:	Nej
Clamp position fixed:	Nej

Luminaire hook mounting:

Nej

Special application:

None