


# Socket outlet

Euro socket outlet, 3-gang, shuttered, screwless terminals, branching terminals, white matt



**Typ:** 303UC-884

**Produkt ID:** 2TKA00002906

**GTIN:** 6438199004624



3-gang Euro socket outlet with center plate. There are terminals for each contact of the socket outlet for max 4 rigid wires and 2 X-terminals for 2-rigid wires. The socket outlet insert without the cover plate is screen-protected.

## Teknisk specifikation

### Elektriska värden

Nominal current:	2.5 A
Nominal voltage:	250 V

### Klassificering

Suitable for degree of protection (IP):	IP21
---	------

### Packning

Förpackning:	1/10/100/1800
Enhet:	st

### ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC000125
Model:	EURO plug (CEE 7/16)
Number of active pins (round):	2
With signal lamp:	Nej
Number of units:	3
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Nej
With enhanced contact protection:	Ja
Label space/information surface:	Nej
Colour:	White
RAL-number (similar):	9016
Metallic colour:	Nej
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	Nej
With loop through function:	Nej
With on/off switch:	Nej

# Produktblad

Euro socket outlet, 3-gang, shuttered, screwless terminals, branching terminals, white matt



Rotated central insert:	Nej
Frequency:	50 Hz
Device width:	71 mm
Device height:	35 mm
Device depth:	71 mm
Min. depth of built-in installation box:	23 mm