

Socket outlet

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, painted steel



Typ: 302EUJ-866

Produkt ID: 2TKA00002908

GTIN: 6438199004648



There are terminals for each contact of the socket outlet for max 4 rigid wires. No X-terminals. The socket outlet insert without the cover plate is screen-protected.

Teknisk specifikation

Elektriska värden

Nominal current:	16 A
Nominal voltage:	250 V

Klassificering

Suitable for degree of protection (IP):	IP21
Protection class:	IP21

Packning

Förpackning:	1/10/100/1200
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	Nej
Number of units:	2
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Nej
With enhanced contact protection:	Ja
Label space/information surface:	Nej
Colour:	Stainless steel
Metallic colour:	Ja
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with claw and screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	Nej
With loop through function:	Nej
With on/off switch:	Nej
Rotated central insert:	Nej
Frequency:	50 Hz
Device width:	85 mm

Produktblad

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, painted steel



Device height:	48 mm
Device depth:	100 mm
Min. depth of built-in installation box:	17 mm
