

# Mounting box

Mounting box for hollow walls, hole Ø74 mm



**Typ:** AUS74.2

**Produkt ID:** 2TKA00003482

**GTIN:** 6438199005041



AUS74.2 is a front-mounted mounting box with a telescopic bottom part for walls of 1–3 plasterboards (wall thickness 9–39 mm). Due to the telescopic bottom part, the depth of the box can be adjusted between 54mm and 70 mm. Mounting hole diameter 73–74 mm (normal box drill).

The protection rating of the box is IP3X. Made from halogen-free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test

according to the IEC/EN 60670 standard: 2005 (850 °C).

## Teknisk specifikation

### Elektriska värden

Operating voltage:	400 V
--------------------	-------

### Thermal conditions

Operating temperature:	-25 ... 90 °C
------------------------	---------------

### Dimensions

For plastic pipe:	Ø16/20mm
-------------------	----------

**Packning**

Förpackning:	60
Enhet:	st

**ETIM Data**

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601
Mounting method:	Flush mounted (plaster)
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	Nej
Connectable:	Ja
Equipped with:	None
Diameter:	74 mm
Length:	73 mm
Width:	73 mm
Depth:	73 mm
Inner depth:	52 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Ja
Housing feed-through by break-out opening:	Nej
Housing feed-through by seal membrane:	Nej
Housing feed-through by nozzle:	Nej
Housing feed-through by step membrane:	Nej
For tube diameter:	20 mm
Suitable for cable diameter:	8 mm
Pipe locking:	Ja
Pipe locking optional:	Nej
Inlet from the rear:	Ja
Material:	Plastic
Halogen free:	Ja
Surface protection:	Untreated

# Produktblad

Mounting box for hollow walls, hole Ø74 mm



Colour:	White
Degree of protection (IP):	IP3X
Transparent cover:	Nej
Sealable:	Nej
With screening:	Nej
Air tight:	Nej
Clamp position fixed:	Nej
Luminaire hook mounting:	Nej
Special application:	None