

Switch

Universal switch, 1-fold



Typ: FAK1021

Produkt ID: 2TKA00003792

GTIN: 6438199005218



Universal switch with one change over contact. Good marking possibilities. Nominal voltage of LED: 24 V ac/dc (operates 8 – 30 V ac/dc, brightness changes). Loading capacity of switch (max) 30 V ac / 35 V dc, 100 mA ac/dc, 3 VA / 3 W.

Teknisk specifikation

Elektriska värden

Nominal voltage:	24 V
------------------	------

Klassificering

Suitable for degree of protection (IP):	IP20
---	------

Signal products

Loading capacity of switch (max):	30 Vac / 35 Vdc, 100 mA ac/dc
Operating voltage of signal lamp:	9,5 - 28 V ac / 9,5 - 35 V dc
Current drain of signal lamp:	10 mA ac / 10 mA dc

Packning

Förpackning:	1/10/100/1200
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000029
Assembly arrangement:	Basic element with full cover plate
Model:	Single push button
Method of operation:	Push button
Number of contacts as normally closed contact:	4
Number of contacts as change-over contact:	1
Contactless type:	Nej
Number of rockers:	1
Number of poles:	1
Rated current:	1 A
With lighting:	Nej
With light source:	Nej
With signal lamp:	Nej
Feedback-signal contact:	Ja
Connection type:	Screwed terminal
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Anti-bacterial treatment:	Nej
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	White
RAL-number (similar):	9010
Transparent:	Nej
Label space/information surface:	Ja
Imprint:	None
Impact strength:	IK00
Device width:	71 mm
Device height:	39 mm
Device depth:	71 mm

Min. depth of built-in installation box:	21 mm
Compatible with Apple HomeKit:	Nej
Compatible with Google Assistant:	Nej
Compatible with Amazon Alexa:	Nej
IFTTT support available:	Nej