
Socket outlet

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, matt black

Typ: 302EUJT-885

Produkt ID: 2TKA00003863

GTIN: 6438199005348



There are terminals for each contact of the socket outlet for max 4 rigid wires. The socket outlet insert without the cover plate is screen-protected. Very flat construction. Installation in special 1,5X mounting box.

Teknisk specifikation

Elektriska värden

Nominal current:	16 A
Nominal voltage:	250 V

Klassificering

Suitable for degree of protection (IP):	IP21
---	------

Packning

Förpackning:	1/10/100/1200
Enhet:	st

ETIM Data

ETIM Version:	ETIM-8.0
---------------	----------



ETIM Class:	EC000125
Model:	Protective contact (type F)
Protective contact:	Ja
Protective earth pin round:	Nej
With signal lamp:	Nej
With built-in USB power supply:	Nej
Number of units:	2
Number of modules (module system):	1
Number of phases:	1
Connection type:	Push-in clamp
With hinged lid:	Nej
With enhanced contact protection:	Ja
Label space/information surface:	Nej
Colour:	Black
RAL-number (similar):	9005
Metallic colour:	Nej
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Ja
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Flush mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Lacquered
Surface finishing:	Matt
Anti-bacterial treatment:	Nej

Produktblad

Socket outlet, Schuko, 2-gang, shuttered, screwless terminals, branching terminals, flat, matt black



With on/off switch:	Nej
With loop through function:	Nej
Rotated central insert:	Nej
Frequency:	50 Hz
Device width:	120 mm
Device height:	80 mm
Device depth:	40 mm
Min. depth of built-in installation box:	17 mm