

# Junction box

Junction box for EI60 and EI30 fire rated ceilings

Typ: AU70FR

Produkt ID: 2TKA00003942

GTIN: 6438199005911



The box has two screw towers with c/c 70mm (for M4 screws), which fits all standard ceiling covers and lamp outlets (also DCL standard). Installation hole with a hole saw and reworking of the hole is forbidden (specified hole saw Ø84mm, drill hole max. 86mm). The box shall be installed to the center of the drill hole. The green adapter ring supplied with the box is used with single plaster board ceiling (12.5mm), and the ring is removed with double plaster board (2 x 12.5mm). If the plaster boards are 15mm thick, a red adapter ring is also used; in one position the lift is 2.5mm (1 x 15mm plate) and in another position 5mm (2 x 15mm plate). The box has one opened inlet for a 16/20 mm tube, and totally 8 fixed inlets. The box comes with a lid AU67.70.

Manufactured from halogen free material (IEC/61249-2-21), the box complies with the IEC/EN60670:2005 glow wire test (850 °C).

## Teknisk specifikation

### Elektriska värden

Rated voltage:	400 V
----------------	-------

### Thermal conditions

Operating temperature:	-25 ... 90 °C
------------------------	---------------

## Dimensions

For plastic pipe:	Ø16/20mm
-------------------	----------

## Packning

Förpackning:	20
Enhet:	st

## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601
Mounting method:	Other
Shape:	Round
Construction type:	Cable junction box
Model:	Single
Provided with revolving ring:	Nej
Connectable:	Nej
Equipped with:	None
Diameter:	92 mm
Length:	120 mm
Width:	120 mm
Depth:	120 mm
Inner depth:	50 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Nej
Housing feed-through by break-out opening:	Nej
Housing feed-through by seal membrane:	Nej
Housing feed-through by nozzle:	Ja
Housing feed-through by step membrane:	Nej
For tube diameter:	16 mm
Pipe locking:	Ja
Pipe locking optional:	Nej
Inlet from the rear:	Nej

Number of inlets:	8
Number of included spouts:	8
Material:	Plastic
Halogen free:	Ja
Surface protection:	Untreated
Colour:	Red
Degree of protection (IP):	IP3X
Cover model:	Construction protective cover
Transparent cover:	Nej
Cover attachment:	Snapped on
Sealable:	Nej
Circuit integrity:	E60
With screening:	Nej
Air tight:	Nej
Clamp position fixed:	Nej
Luminaire hook mounting:	Nej
Special application:	Fire protection