

Combination thermostat

Combination thermostat, 16A, floor sensor, Jussi



Typ: TC16-20-214

Produkt ID: 2TKA00004034

GTIN: 6438199005966



Thermostat with low insert (20 mm mounting depth) meeting the Ecodesign requirements. The thermostat is pre-programmed. Rated voltage 230 V AC \pm 10% 50 Hz

Output 1 no and connectors 1.5 mm² to 4 mm²

Switching current 250 V AC / 16 (2) A, protection class II and protection class IP21.

Operating temperature 0 ° C to 35 ° C and storage temperature -20 ° C to 70 ° C

Clock Accuracy (at 20 ° C) \pm 0.5 sec / min

Power consumption (standby) <0.05 W

Floor sensor NTC 10k Ω @ 25 ° C and external control (EXT connector) 230V AC / 10 μ A (same phase).

Teknisk specifikation

Packning

Förpackning:	1/10
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC011309
Regulation type on/off:	Nej

Regulation type modulating:	Ja
Type of power supply:	Other
Connection:	3-/4-wire
With receiver:	Nej
Measuring range:	5...35 °C
External sensor:	Ja
With thermal feedback:	Ja
Suitable for heating:	Ja
Number of heater outputs:	1
Suitable for cooling:	Nej
Selector switch for heating and heating with hot water:	Nej
Sensor/feeler type:	Resistance sensor
Temperature readable:	Ja
Relative humidity (RH) readable:	Nej
With display:	Ja
Type of clock:	Week clock
Clock model:	Digital
Overtime switch:	Nej
Optimisation:	Ja
With tap water circuit:	Nej
Operation:	Button
Weather-dependent control system:	Nej
Number of switching programmes:	7
Contact type:	Normally open contact (NO)
Degree of protection (IP):	IP21
Explosion-proof:	Nej
Colour:	White
RAL-number:	9010
Width:	85 mm
Depth:	85 mm
Height:	38 mm
Class of the temperature control:	I
Standby power consumption (solstandby):	0.05 W
Compatible with Apple HomeKit:	Nej

Produktblad

Combination thermostat, 16A, floor sensor, Jussi



Compatible with Google Assistant:	Nej
Compatible with Amazon Alexa:	Nej
IFTTT support available:	Nej
