

Switch

1-gang intermediate switch, 16AX/250V, Impressivo, 2 X-terminals, black matt



Typ: 1067UC-885

Produkt ID: 2TKA00004465

GTIN: 6438199008639



Switch with screwless terminals. The terminals are for max 2 rigid wires. Including switch insert and rocker.

Teknisk specifikation

Elektriska värden

| | |
|------------------|-------|
| Nominal voltage: | 250 V |
| Rated current: | 16 AX |

Klassificering

| | |
|-----------------------------------------|------|
| Suitable for degree of protection (IP): | IP21 |
|-----------------------------------------|------|

Packning

| | |
|--------------|---------------|
| Förpackning: | 1/10/100/1800 |
| Enhet: | st |

ETIM Data

| | |
|----------------------|---------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC001590 |
| Wiring system: | Other |
| Method of operation: | Rocker/button |

| | |
|------------------------------------------|----------------------------------------|
| Assembly arrangement: | Basic element with central cover plate |
| Push button switch: | Nej |
| Number of rockers: | 1 |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Screw mounting |
| With mounting plate: | Nej |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Ja |
| Surface protection: | Lacquered |
| Surface finishing: | Matt |
| Colour: | Black |
| RAL-number (similar): | 9016 |
| Label space/information surface: | No |
| Illumination: | No |
| Rated current: | 16 A |
| Switching current for fluorescent lamps: | 16 AX |
| Feedback-signal contact: | Nej |
| Connection type: | Other |
| Washing machine switch: | Nej |
| Device width: | 70 mm |
| Device height: | 40 mm |
| Device depth: | 70 mm |
| Built-in depth: | 18 mm |
| Min. depth of built-in installation box: | 18 mm |