

# Mounting box

Height 82 mm, screw c/c distance 60 mm

Typ: AUB60H

Produkt ID: 2TKA00004657

GTIN: 6438199008844



Mounting box AUB60H is especially designed for off site and on site casting applications. Box height is 82 mm. Box includes two inlets with locking springs for 20 or 25 mm conduits. Additional inlets can be attached to other sides without need of any tooling. The mounting box includes a rotating, steplessly adjustable extension ring. The extension ring can be tilted 0-4°. Box combinations can be created without additional accessories and box has large inside space. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (650 °C). Maximum number of conductors is 30 pcs.

## Teknisk specifikation

### Thermal conditions

Operating temperature:	-25 ... 90 °C
------------------------	---------------

### Packning

Förpackning:	42
Enhet:	st

### ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601

Mounting method:	Concrete building
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	Ja
Connectable:	Ja
Equipped with:	None
Diameter:	71 mm
Length:	167 mm
Width:	98 mm
Depth:	167 mm
Inner depth:	77 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Ja
Housing feed-through by break-out opening:	Ja
Housing feed-through by seal membrane:	Nej
Housing feed-through by nozzle:	Ja
Housing feed-through by step membrane:	Nej
For tube diameter:	20/25 mm
Pipe locking:	Ja
Pipe locking optional:	Nej
Inlet from the rear:	Nej
Number of inlets:	8
Number of included spouts:	2
Material:	Plastic
Halogen free:	Ja
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP3X
Cover model:	Construction protective cover
Transparent cover:	Nej
Cover attachment:	Snapped on
Sealable:	Nej

# Produktblad

Height 82 mm, screw c/c distance 60 mm



With screening:	Nej
Air tight:	Nej
Clamp position fixed:	Nej
Luminaire hook mounting:	Nej
Special application:	None