

Junction box

Height 80 mm, screw c/c distance 67 mm

Typ: AUB67

Produkt ID: 2TKA00004671

GTIN: 6438199008868



Junction box AUB67 is especially designed for off site and on site casting applications. Box height is 80 mm. Box has several fixed inlets with locking springs to two directions (4 x 20 mm and 4 x 25 mm). Two 25 mm inlets have removable 20 mm reducer. It is possible to connect four 20 mm conduits simultaneously to one direction. The mounting box includes a rotating installation ring, has large inside space and removable back cover. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (650 °C). Maximum number of conductors is 40 pcs.

Teknisk specifikation

Thermal conditions

Operating temperature:	-25 ... 90 °C
------------------------	---------------

Packning

Förpackning:	36
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601

Mounting method:	Concrete building
Shape:	Round
Construction type:	Cable junction box
Model:	Single
Provided with revolving ring:	Ja
Connectable:	Ja
Equipped with:	None
Diameter:	125 mm
Length:	200 mm
Width:	125 mm
Depth:	200 mm
Inner depth:	75 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Ja
Housing feed-through by break-out opening:	Ja
Housing feed-through by seal membrane:	Nej
Housing feed-through by nozzle:	Ja
Housing feed-through by step membrane:	Nej
For tube diameter:	20/25 mm
Pipe locking:	Ja
Pipe locking optional:	Nej
Inlet from the rear:	Nej
Number of inlets:	8
Number of included spouts:	8
Material:	Plastic
Halogen free:	Ja
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP3X
Cover model:	Construction protective cover
Transparent cover:	Nej
Cover attachment:	Snapped on
Sealable:	Nej

Produktblad

Height 80 mm, screw c/c distance 67 mm



With screening:	Nej
Air tight:	Nej
Clamp position fixed:	Nej
Luminaire hook mounting:	Nej
Special application:	None