

---

# AUD14-03

Prefabricated socket outlet unit Without imprint Protective contact (SCHUKO) Orange - Impressivo



**Typ:** AUD14-03

**Produkt ID:** 2TKA00005312

**GTIN:** 6438199013886

AUD14-03 Prefabricated socket outlet unit, 8-gang Schuko, orange

## Teknisk specifikation

### Elektriska värden

|                  |       |
|------------------|-------|
| Nominal current: | 16 A  |
| Nominal voltage: | 250 V |

### Klassificering

|   |      |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

### ETIM Data

|                                      |               |
|--------------------------------------|---------------|
| ETIM Version:                        | ETIM-9.0      |
| ETIM Class:                          | EC000125      |
| Number of active pins (round):       | 2             |
| With signal lamp:                    | Nej           |
| Number of socket outlets switchable: | 1             |
| Number of phases:                    | 1             |
| Imprint/indication:                  | None          |
| Connection type:                     | Push-in clamp |
| With hinged lid:                     | Nej           |
| With enhanced contact protection:    | Ja            |

|                                  |                            |
|----------------------------------|----------------------------|
| Label space/information surface: | Nej                        |
| Colour:                          | Orange                     |
| RAL-number (similar):            | 2000                       |
| Metallic colour:                 | Nej                        |
| Transparent:                     | Nej                        |
| Lockable:                        | Nej                        |
| Eject-mechanism:                 | Nej                        |
| Insulated mounting:              | Nej                        |
| With function lighting:          | Nej                        |
| With orientation lighting:       | Nej                        |
| Over voltage protection:         | Nej                        |
| Fault current protection:        | Nej                        |
| With miniature fuse:             | Nej                        |
| Special power supply:            | No special power supply    |
| Mounting method:                 | Wall duct                  |
| Type of fastening:               | Snap mounting (engagement) |
| Material:                        | Plastic                    |
| Material quality:                | Thermoplastic              |
| Halogen free:                    | Ja                         |
| Surface protection:              | Untreated                  |
| Surface finishing:               | Glossy                     |
| Anti-bacterial treatment:        | Nej                        |
| With loop through function:      | Nej                        |
| With on/off switch:              | Nej                        |
| Rotated central insert:          | Nej                        |
| Frequency:                       | 50 Hz                      |
| Device width:                    | 45 mm                      |
| Device height:                   | 85 mm                      |
| Device depth:                    | 430 mm                     |