

AUD14-06

Prefabricated socket outlet unit Without imprint Protective contact (SCHUKO) Blue - Impressivo



Typ: AUD14-06

Produkt ID: 2TKA00005314

GTIN: 6438199013909

AUD14-06 Prefabricated socket outlet unit, 8-gang Schuko, blue

Teknisk specifikation

Elektriska värden

| | |
|------------------|-------|
| Nominal current: | 16 A |
| Nominal voltage: | 250 V |

Klassificering

| | |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

ETIM Data

| | |
|--------------------------------------|---------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC000125 |
| Number of active pins (round): | 2 |
| With signal lamp: | Nej |
| Number of socket outlets switchable: | 1 |
| Number of phases: | 1 |
| Imprint/indication: | None |
| Connection type: | Push-in clamp |
| With hinged lid: | Nej |
| With enhanced contact protection: | Ja |

| | |
|----------------------------------|----------------------------|
| Label space/information surface: | Nej |
| Colour: | Blue |
| RAL-number (similar): | 5007 |
| Metallic colour: | Nej |
| Transparent: | Nej |
| Lockable: | Nej |
| Eject-mechanism: | Nej |
| Insulated mounting: | Nej |
| With function lighting: | Nej |
| With orientation lighting: | Nej |
| Over voltage protection: | Nej |
| Fault current protection: | Nej |
| With miniature fuse: | Nej |
| Special power supply: | No special power supply |
| Mounting method: | Wall duct |
| Type of fastening: | Snap mounting (engagement) |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Ja |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Anti-bacterial treatment: | Nej |
| With loop through function: | Nej |
| With on/off switch: | Nej |
| Rotated central insert: | Nej |
| Frequency: | 50 Hz |
| Device width: | 45 mm |
| Device height: | 85 mm |
| Device depth: | 430 mm |