

# Socket outlet

Socket outlet Without imprint White - Saga



**Typ:** 20EUJW-916

**Produkt ID:** 2TKA00005355

**GTIN:** 6438199014111



The socket outlet is equipped with a lid making it a IP44 class device. There are terminals for each contact of the socket outlet. No X-terminals. The terminals are for max 2 rigid wires. The socket outlet comes with a frame. Bio-circular plastics used in the frame.

## Teknisk specifikation

### Elektriska värden

|                  |       |
|------------------|-------|
| Nominal current: | 16 A  |
| Nominal voltage: | 250 V |

### Klassificering

|   |      |
|---|------|
| Suitable for degree of protection (IP): | IP44 |
|---|------|

### Packning

|              |           |
|--------------|-----------|
| Förpackning: | 1/10/1200 |
| Enhet:       | st        |

### ETIM Data

|               |          |
|---------------|----------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class:   | EC000125 |

|                                   |                              |
|-----------------------------------|------------------------------|
| Number of active pins (round):    | 2                            |
| With signal lamp:                 | Nej                          |
| Number of units:                  | 1                            |
| Number of phases:                 | 1                            |
| Imprint/indication:               | None                         |
| Connection type:                  | Push-in clamp                |
| With hinged lid:                  | Nej                          |
| With enhanced contact protection: | Ja                           |
| Label space/information surface:  | Nej                          |
| Colour:                           | White                        |
| RAL-number (similar):             | 9003                         |
| Metallic colour:                  | Nej                          |
| Transparent:                      | Nej                          |
| Lockable:                         | Nej                          |
| Eject-mechanism:                  | Nej                          |
| Insulated mounting:               | Nej                          |
| With function lighting:           | Nej                          |
| With orientation lighting:        | Nej                          |
| Over voltage protection:          | Nej                          |
| Fault current protection:         | Nej                          |
| With miniature fuse:              | Nej                          |
| Special power supply:             | No special power supply      |
| Mounting method:                  | Flush mounted (plaster)      |
| Type of fastening:                | Mounting with claw and screw |
| Material:                         | Plastic                      |
| Material quality:                 | Thermoplastic                |
| Halogen free:                     | Ja                           |
| Surface protection:               | Untreated                    |
| Surface finishing:                | Glossy                       |
| Anti-bacterial treatment:         | Nej                          |
| With loop through function:       | Nej                          |
| With on/off switch:               | Nej                          |
| Rotated central insert:           | Nej                          |
| Frequency:                        | 50...60 Hz                   |

|  |       |
|--|-------|
| Device width:                            | 85 mm |
| Device height:                           | 85 mm |
| Device depth:                            | 41 mm |
| Min. depth of built-in installation box: | 28 mm |