


Switch insert

Switch insert, 16AX/250V, 2-pole, 2 X-terminals, lamp possibility



Typ: 1062.21

Produkt ID: 2TKA000130G1

GTIN: 6418677328633



Control switch insert without rocker. All 1-gang rockers fit to the insert, but in control switch use the rocker 1788-xx must be used. The switch insert has separate circuit-breakers for the N- and L-wires and 2 X-terminals. The X-terminals can be used for extending other wires. The signal light can only be set as a search- or signal light, but in control use it must be set as a signal light.

Teknisk specifikation

Elektriska värden

Nominal voltage:	250 V
Rated current:	16 AX

Klassificering

Suitable for degree of protection (IP):	IP20
---	------

Packning

Förpackning:	10/100
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC001590
Wiring system:	Two-way switch
Method of operation:	Rocker/button
Assembly arrangement:	Basic element
Push button switch:	Nej
Number of rockers:	3
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
With mounting plate:	Nej
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Anti-bacterial treatment:	Nej
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	White
RAL-number (similar):	9016
Label space/information surface:	No
Illumination:	Optional
Function lighting:	Control and orientation
Type of lighting:	LED exchangeable
Rated current:	16 A
Switching current for fluorescent lamps:	16 AX
Feedback-signal contact:	Nej
Connection type:	Other
Washing machine switch:	Nej
Device width:	71 mm
Device height:	27 mm
Device depth:	71 mm
Built-in depth:	17 mm
Min. depth of built-in installation box:	17 mm