

Switch

1-gang 2-way switch, Jussi, 2 X-terminals

Typ: 1066U

Produkt ID: 2TKA000194G1

GTIN: 6410021060169



Switch with screwless terminals and rocker with clip-on fastening. The terminals are for max 2 rigid wires. X-terminals are for extending the wires.

Teknisk specifikation

Elektriska värden

Nominal voltage:	250 V
Rated current:	16 AX

Klassificering

Suitable for degree of protection (IP):	IP21
Protection class:	IP21

Packning

Förpackning:	10/100
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC001590
Wiring system:	Two-way switch

Method of operation:	Rocker/button
Assembly arrangement:	Basic element with complete housing
Push button switch:	Nej
Number of rockers:	1
Mounting method:	Flush mounted (plaster)
Type of fastening:	Screw mounting
With mounting plate:	Nej
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Anti-bacterial treatment:	Nej
Surface protection:	Untreated
Surface finishing:	Matt
Colour:	White
RAL-number (similar):	9010
Label space/information surface:	No
Illumination:	Optional
Function lighting:	Control and orientation
Type of lighting:	LED exchangeable
Rated current:	16 A
Switching current for fluorescent lamps:	16 AX
Feedback-signal contact:	Nej
Connection type:	Other
Washing machine switch:	Nej
Device width:	71 mm
Device height:	34 mm
Device depth:	71 mm
Built-in depth:	17 mm
Min. depth of built-in installation box:	17 mm