


Switch

1-gang 2-way switch,16AX/250V, Impressivo, no X-terminals, IP44



Typ: 1066UW-84

Produkt ID: 2TKA000200G1

GTIN: 6438199000022



Switch with screwless terminals and rocker with screw fastening. The terminals are for max 2 rigid wires. Including switch insert, rocker, cover frame and the seals.

Teknisk specifikation

Elektriska värden

| | |
|------------------|-------|
| Nominal voltage: | 250 V |
| Rated current: | 16 AX |

Klassificering

| | |
|---|------|
| Suitable for degree of protection (IP): | IP44 |
|---|------|

Packning

| | |
|--------------|---------------|
| Förpackning: | 1/10/100/1200 |
| Enhet: | st |

ETIM Data

| | |
|----------------|----------------|
| ETIM Version: | ETIM-9.0 |
| ETIM Class: | EC001590 |
| Wiring system: | Two-way switch |

| | |
|--|-------------------------------------|
| Method of operation: | Rocker/button |
| Assembly arrangement: | Basic element with full cover plate |
| Push button switch: | Nej |
| Number of rockers: | 1 |
| Mounting method: | Flush mounted (plaster) |
| Type of fastening: | Screw mounting |
| With mounting plate: | Nej |
| Material: | Plastic |
| Material quality: | Thermoplastic |
| Halogen free: | Ja |
| Anti-bacterial treatment: | Nej |
| Surface protection: | Untreated |
| Surface finishing: | Glossy |
| Colour: | White |
| RAL-number (similar): | 9016 |
| Label space/information surface: | No |
| Illumination: | Optional |
| Function lighting: | Control and orientation |
| Type of lighting: | LED exchangeable |
| Rated current: | 16 A |
| Switching current for fluorescent lamps: | 16 AX |
| Feedback-signal contact: | Nej |
| Connection type: | Other |
| Washing machine switch: | Nej |
| Device width: | 85 mm |
| Device height: | 35 mm |
| Device depth: | 85 mm |
| Built-in depth: | 17 mm |
| Min. depth of built-in installation box: | 17 mm |