

# Tele outlet

Supporting frame insert for 2xRJ45,  
Systemax



**Typ:** 1819.04

**Produkt ID:** 2TKA000602G1

**GTIN:** 6418677335945



Tele outlet for two Systemax RJ45 connectors. Compatible with the center plates 1819-xx.

## Teknisk specifikation

### Klassificering

|   |      |
|---|------|
| Suitable for degree of protection (IP): | IP20 |
|---|------|

### Packning

|              |        |
|--------------|--------|
| Förpackning: | 10/100 |
| Enhet:       | st     |

### ETIM Data

|                       |               |
|-----------------------|---------------|
| ETIM Version:         | ETIM-9.0      |
| ETIM Class:           | EC000018      |
| Assembly arrangement: | Basic element |
| Utilization:          | Modular Jack  |
| Support ring:         | Nej           |
| With dust cover:      | Nej           |
| With hinged lid:      | Nej           |

|  |                          |
|--|--------------------------|
| Outlet direction:                        | Straight                 |
| Imprintable label:                       | Without indication field |
| With imprint:                            | Nej                      |
| Mounting method:                         | Flush mounted (plaster)  |
| Material:                                | Plastic                  |
| Material quality:                        | Thermoplastic            |
| Halogen free:                            | Ja                       |
| Anti-bacterial treatment:                | Nej                      |
| Surface protection:                      | Untreated                |
| Surface finishing:                       | Glossy                   |
| Colour:                                  | White                    |
| RAL-number (similar):                    | 9010                     |
| Transparent:                             | Nej                      |
| Type of fastening:                       | Mounting with screw      |
| With buses/couplings:                    | Nej                      |
| Suitable for number of connectors:       | 2                        |
| With strain relief:                      | Nej                      |
| Shielded buses:                          | Nej                      |
| Shielded housing:                        | Nej                      |
| Luster terminal:                         | Nej                      |
| With lighting:                           | Nej                      |
| Impact strength:                         | IK00                     |
| Device width:                            | 70 mm                    |
| Device height:                           | 70 mm                    |
| Device depth:                            | 24 mm                    |
| Min. depth of built-in installation box: | 12 mm                    |