

# Socket outlet

Socket outlet, Jussi IP55, 2-gang Schuko, shuttered, screwless terminals, branching terminals



**Typ:** 402ESW

**Produkt ID:** 2TKA000996G1

**GTIN:** 6418677334580



There are terminals for each contact of the socket outlet for max 4 rigid wires. 1 potential free X-terminal with screw connector. IP55 when lids are closed and installed horizontally (lids opening upwards). The lids are kept closed with a return spring when socket outlet is not in use.

## Teknisk specifikation

### Elektriska värden

Nominal current:	16 A
Nominal voltage:	250 V

### Klassificering

Suitable for degree of protection (IP):	IP55
---	------

### Packning

Förpackning:	10/100
Enhet:	st

### ETIM Data

ETIM Version:	ETIM-9.0
---------------	----------

ETIM Class:	EC000125
Number of active pins (round):	2
With signal lamp:	Nej
Number of units:	2
Number of phases:	1
Imprint/indication:	None
Connection type:	Push-in clamp
With hinged lid:	Nej
With enhanced contact protection:	Ja
Label space/information surface:	Nej
Colour:	White
RAL-number (similar):	9010
Metallic colour:	Nej
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Nej
With loop through function:	Nej
With on/off switch:	Nej
Rotated central insert:	Nej

# Produktblad

Socket outlet, Jussi IP55, 2-gang Schuko, shuttered, screwless terminals, branching terminals



Frequency:	50 Hz
Device width:	80 mm
Device height:	50 mm
Device depth:	109 mm