

# Ceiling rose cover

Ceiling rose, earthed, bipolar, IP20



**Typ:** AKK13J

**Produkt ID:** 2TKA001668G1

**GTIN:** 6410011525135



The AKK13J lighting ceiling rose features screwless block technology, which makes installation faster and easier. Ceiling rose AKK13J (IP 20) is suitable for both flush and surface mounting. Smallest compatible conductor size 1.5 mm<sup>2</sup>.

## Teknisk specifikation

### Elektriska värden

Nominal current:	6 A
Nominal voltage:	250 V

### Klassificering

Suitable for degree of protection (IP):	IP20
---	------

### Packning

Förpackning:	5/50
Enhet:	st

### ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC000125
With signal lamp:	Nej

Number of units:	1
Number of socket outlets switchable:	1
Number of phases:	1
Imprint/indication:	None
With hinged lid:	Nej
With enhanced contact protection:	Nej
Label space/information surface:	Nej
Colour:	White
RAL-number (similar):	9010
Metallic colour:	Nej
Transparent:	Nej
Lockable:	Nej
Eject-mechanism:	Nej
Insulated mounting:	Nej
With function lighting:	Nej
With orientation lighting:	Nej
Over voltage protection:	Nej
Fault current protection:	Nej
With miniature fuse:	Nej
Special power supply:	No special power supply
Mounting method:	Surface mounted (plaster)
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	Ja
Surface protection:	Untreated
Surface finishing:	Matt
Anti-bacterial treatment:	Nej
With loop through function:	Nej
With on/off switch:	Nej
Rotated central insert:	Nej
Frequency:	50...60 Hz
Impact strength:	IK00
Device width:	115 mm

# Produktblad

Ceiling rose, earthed, bipolar, IP20



---

Device height:	50 mm
Device depth:	115 mm
Min. depth of built-in installation box:	10 mm

---