


Junction box

Ceiling junction box for 13/26 mm board

Typ: AU70

Produkt ID: 2TKA001748G1

GTIN: 6418677332357



The ceiling junction box has two screw pillars for M4 screws, e.g. for attaching lamp connectors or roof lids and screw distance is c/c 70 mm. The green adapter ring, delivered with the box, is used when board thickness is 12-13 mm. The ring is removed when the board thickness is 24-26 mm e.g. double plaster board. There are 8 fixed inlets for 20 mm conduits, and 6 have an adapter for 16 mm conduit. All inlets are equipped with a locking device in metal for reliable connection between the conduits (flexi or stiff pipe) and the box. In addition, there are two knock outs in the bottom for different inlets. Manufactured from halogen free material (IEC/61249-2-21), the box complies with the IEC/EN60670:2005 glow wire test (850 °C).

Teknisk specifikation

Elektriska värden

Rated voltage: 400 V

Thermal conditions

Operating temperature: -25 ... 90 °C

Dimensions

For plastic pipe: Ø16/20mm

Packning

Förpackning:	50
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601
Mounting method:	Flush mounted (plaster)
Shape:	Round
Construction type:	Cable junction box
Model:	Single
Provided with revolving ring:	Nej
Connectable:	Nej
Equipped with:	None
Diameter:	92 mm
Length:	120 mm
Width:	120 mm
Depth:	120 mm
Inner depth:	53 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Nej
Housing feed-through by break-out opening:	Nej
Housing feed-through by seal membrane:	Nej
Housing feed-through by nozzle:	Ja
Housing feed-through by step membrane:	Nej
For tube diameter:	16 mm
Pipe locking:	Ja
Pipe locking optional:	Nej
Inlet from the rear:	Ja
Number of inlets:	8
Number of included spouts:	8
Material:	Plastic
Halogen free:	Ja

Surface protection:	Untreated
Colour:	Blue
Degree of protection (IP):	IP3X
Cover model:	Construction protective cover
Transparent cover:	Nej
Cover attachment:	Snapped on
Sealable:	Nej
With screening:	Nej
Air tight:	Nej
Clamp position fixed:	Nej
Luminaire hook mounting:	Nej
Special application:	None