
Control Unit

Control Unit, 2-loop

Typ: FEH1002

Produkt ID: 2TKA002110G1

GTIN: 6410070607124



The loop controls itself against short circuits and breaks. Possibility to connect both closing and opening potential free contacts. Input delay 150 ms / 2,5 s. Memory/no memory function. Potential free output. Cancelling button with LED. Good marking possibilities on the button and name plate. Operating voltage: 15 - 28 V ac / 18 - 35 V dc. Current consumption: 110 mA ac / 60 mA dc.

Teknisk specifikation

Elektriska värden

Operating voltage:	15 - 28 V ac / 18 - 35 V dc
Current consumption:	110 mA ac / 60 mA dc

Klassificering

Enclosure class:	IP20
------------------	------

Dimensions

Dimensions:	71x71x39 mm
Weight:	50 g

Thermal conditions

Operating temperature:	5 ... 40 °C
Storage temperature:	-40 ... 70 °C

Signal products

Load capacity of power supply:	1,0 A ac/dc, 30 VA / W
Load capacity of potential free contact:	1,0 A ac/dc, 42 V ac / 60 V dc, 30 VA / W
Loop's closed circuit current:	≥ 5 mA
Loop's terminator:	≥ 1 kΩ
Alarm delay:	0,1 / 2,5 s (valittavissa silmukkohtaisesti)
Loop's memory function:	on / off

Packning

Förpackning:	1/10/100/1200
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002247
Model:	Regulating combination
Colour:	White
RAL-number (similar):	9010
Voltage type:	AC/DC
With transformer:	Nej
Degree of protection (IP):	IP20
Device width:	71 mm
Device height:	71 mm
Device depth:	39 mm