

---

# Leak Guard

---

**Typ:** FEH2100

**Produkt ID:** 2TKA002115G1

**GTIN:** 6410070607131



The Leak Guard unit operates as the standard Control Unit FEH1001, with the exception that the loop monitors leakage current (10  $\mu$ A). Tape sensors, conduit pairs or other leakage sensors could be connected to the device. Memory/no memory function. Potential free output. Cancelling button with LED. Operating voltage: 9.5 - 28 V ac / 9.5 - 35 V dc. Current consumption: 75 mA ac / 40 mA dc. Good marking possibilities on the button and name plate.

## Teknisk specifikation

### Elektriska värden

|                      |                     |
|----------------------|---------------------|
| Current consumption: | 70 mA ac / 40 mA dc |
|----------------------|---------------------|

### Klassificering

|                  |      |
|------------------|------|
| Enclosure class: | IP20 |
|------------------|------|

### Dimensions

|             |             |
|-------------|-------------|
| Dimensions: | 71x71x39 mm |
|-------------|-------------|

|         |      |
|---------|------|
| Weight: | 45 g |
|---------|------|

### Thermal conditions

|                        |             |
|------------------------|-------------|
| Operating temperature: | 5 ... 40 °C |
|------------------------|-------------|

|                      |               |
|----------------------|---------------|
| Storage temperature: | -40 ... 70 °C |
|----------------------|---------------|

**Signal products**

|  |   |
|--|---|
| Load capacity of power supply:           | 1,0 A ac/dc, 30 VA / W                    |
| Load capacity of potential free contact: | 1,0 A ac/dc, 42 V ac / 60 V dc, 30 VA / W |
| Alarm delay:                             | 0,1 s (ei viiveen valintaa)               |
| Loop's memory function:                  | on / off                                  |
| Loop's action limit:                     | 5 ... 10 $\mu$ A                          |

**Packning**

|              |               |
|--------------|---------------|
| Förpackning: | 1/10/100/1200 |
| Enhet:       | st            |

**ETIM Data**

|                                   |                  |
|-----------------------------------|------------------|
| ETIM Version:                     | ETIM-9.0         |
| ETIM Class:                       | EC001764         |
| Type of messaging:                | Water            |
| Mounting method:                  | Surface mounting |
| Indication:                       | Optic/acoustic   |
| Operating voltage:                | 24 V             |
| Colour:                           | White            |
| Height:                           | 71 mm            |
| Width:                            | 71 mm            |
| Depth:                            | 45 mm            |
| Compatible with Apple HomeKit:    | Nej              |
| Compatible with Google Assistant: | Nej              |
| Compatible with Amazon Alexa:     | Nej              |
| IFTTT support available:          | Nej              |