

# Mounting box

Mounting box for board walls



Typ: AUS15.2

Produkt ID: 2TKA130020G1

GTIN: 6410011523841



The AUS15.2 mounting box is used in buildings that have board walls. The holes are made with a hole saw (diameter 70mm). After the required conduit or cable inlets have been knocked out, the box is inserted in the hole. Turning the screws clockwise tightens the fastener against the board and secures the box in place. Conduits and cables are attached by using inlets that are pushed through from inside the box. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).

## Teknisk specifikation

### Packning

|              |    |
|--------------|----|
| Förpackning: | 50 |
| Enhet:       | st |

### ETIM Data

|                               |                                      |
|-------------------------------|--------------------------------------|
| ETIM Version:                 | ETIM-9.0                             |
| ETIM Class:                   | EC002601                             |
| Mounting method:              | Flush mounted (plaster)              |
| Shape:                        | Round                                |
| Construction type:            | Device connection box (round/square) |
| Model:                        | Single                               |
| Provided with revolving ring: | Nej                                  |

|                                            |           |
|--------------------------------------------|-----------|
| Connectable:                               | Ja        |
| Equipped with:                             | None      |
| Diameter:                                  | 71 mm     |
| Length:                                    | 71 mm     |
| Width:                                     | 71 mm     |
| Depth:                                     | 71 mm     |
| Inner depth:                               | 41 mm     |
| For number of electric fittings:           | 1         |
| Mounting switching equipment:              | Screwing  |
| With screws:                               | Ja        |
| Housing feed-through by break-out opening: | Ja        |
| Housing feed-through by seal membrane:     | Nej       |
| Housing feed-through by nozzle:            | Nej       |
| Housing feed-through by step membrane:     | Nej       |
| For tube diameter:                         | 20 mm     |
| Suitable for cable diameter:               | 8 mm      |
| Pipe locking:                              | Nej       |
| Pipe locking optional:                     | Nej       |
| Inlet from the rear:                       | Ja        |
| Material:                                  | Plastic   |
| Halogen free:                              | Ja        |
| Surface protection:                        | Untreated |
| Colour:                                    | White     |
| Degree of protection (IP):                 | IP3X      |
| Transparent cover:                         | Nej       |
| Sealable:                                  | Nej       |
| With screening:                            | Nej       |
| Air tight:                                 | Nej       |
| Clamp position fixed:                      | Nej       |
| Luminaire hook mounting:                   | Nej       |
| Special application:                       | None      |