

Mounting box

Mounting box for board walls



Typ: AUS15.2

Produkt ID: 2TKA130020G1

GTIN: 6410011523841



The AUS15.2 mounting box is used in buildings that have board walls. The holes are made with a hole saw (diameter 70mm). After the required conduit or cable inlets have been knocked out, the box is inserted in the hole. Turning the screws clockwise tightens the fastener against the board and secures the box in place. Conduits and cables are attached by using inlets that are pushed through from inside the box. Made of halogen free material (IEC/61249-2-21) and fulfills the requirements of the glow wire test according to the standard IEC/EN60670: 2005 (850 °C).

Teknisk specifikation

Packning

Förpackning:	50
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002601
Mounting method:	Flush mounted (plaster)
Shape:	Round
Construction type:	Device connection box (round/square)
Model:	Single
Provided with revolving ring:	Nej

Connectable:	Ja
Equipped with:	None
Diameter:	71 mm
Length:	71 mm
Width:	71 mm
Depth:	71 mm
Inner depth:	41 mm
For number of electric fittings:	1
Mounting switching equipment:	Screwing
With screws:	Ja
Housing feed-through by break-out opening:	Ja
Housing feed-through by seal membrane:	Nej
Housing feed-through by nozzle:	Nej
Housing feed-through by step membrane:	Nej
For tube diameter:	20 mm
Suitable for cable diameter:	8 mm
Pipe locking:	Nej
Pipe locking optional:	Nej
Inlet from the rear:	Ja
Material:	Plastic
Halogen free:	Ja
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP3X
Transparent cover:	Nej
Sealable:	Nej
With screening:	Nej
Air tight:	Nej
Clamp position fixed:	Nej
Luminaire hook mounting:	Nej
Special application:	None