

Junction box

Junction box IP65, grey

Typ: AP10/G

Produkt ID: 2TKA140003G1

GTIN: 6418677307287



The square junction box AP10/G (6,0 mm², 500 V) is equipped with 12 membrane cable entries (Ø 19 mm) in the sides, and two on the bottom. Cables are easy to connect by simply inserting the stripped ends through the inlets. The box locks by snapping and can be opened by inserting a screwdriver (for example) into the opening slots - no screws are needed. The box can be furnished with strain-reliefs AS9.10, AS9, AS9.1 and AS9.3. Mounting temperature -25...+60 °C. Made of halogen free material (IEC/61249-2-21)

Teknisk specifikation

Elektriska värden

Rated voltage:	500 V
Wire range:	6 mm ²

Klassificering

Enclosure class:	IP65
------------------	------

Dimensions

Dimensions:	104 x 104 mm
-------------	--------------

Colors

Colour:	Grey
Colour code:	RAL7035

Packning

Förpackning:	5/30
Enhet:	st

ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002600
Model:	Junction box
Equipped with:	None
Shape:	Square
Mounting method:	Universal
Mounting in the soil:	Nej
Mounting under water:	Nej
For tube diameter:	19 mm
Inlet from the rear:	Ja
Length:	48 mm
Width:	104 mm
Depth:	104 mm
Tackable:	Nej
Number of inlets:	12
Type of housing feed-through:	Seal membrane
Material:	Plastic
Halogen free:	Ja
Surface protection:	Untreated
Colour:	Grey
Degree of protection (IP):	IP65
Cover model:	Blind cover
Transparent cover:	Nej
Cover attachment:	Snapped on

Castable:	Nej
With casting compound:	Nej
Sealable:	Ja
Rated insulation voltage Ui:	500 V
With screening:	Nej
Weatherproof:	Ja
Operating temperature:	-25...60 °C
Explosion-tested version:	Nej