

# Junction box IP65

Surface-mounted junction box, IP65, 86 x 86 mm, white



Typ: AP9

Produkt ID: 2TKA140012G1

GTIN: 6410016125095



The square junction box AP9 (2,5 mm<sup>2</sup>, 500 V) is equipped with 12 membrane cable entries for cables up to Ø 17 mm in the sides, and two at the bottom for cables up to Ø 19 mm. Cables are easy to connect by simply inserting the stripped ends through the inlets. The box locks by snapping and can be opened by inserting a screwdriver (for example) into the opening slots - no screws are needed. The box can be furnished with strain-reliefs AS9.10, AS9, AS9.1 and AS9.3, which fits for Ø 6 - 15,5 mm cable. VDE-approved. Mounting temperature -25...+60 °C. Made of halogen free material (IEC/61249-2-21).

## Teknisk specifikation

### Elektriska värden

Rated voltage:	500 V
Wire range:	2.5 mm <sup>2</sup>

### Klassificering

Enclosure class:	IP65
------------------	------

### Dimensions

Dimensions:	86x86x39 mm
Weight:	58 g

## Thermal conditions

Operating temperature:	-25 ... 60 °C
------------------------	---------------

## Colors

Colour:	White
Colour code:	RAL9003

## Packning

Förpackning:	5/50
Enhet:	st

## ETIM Data

ETIM Version:	ETIM-9.0
ETIM Class:	EC002600
Model:	Junction box
Equipped with:	None
Shape:	Square
Mounting method:	Universal
Mounting in the soil:	Nej
Mounting under water:	Nej
For tube diameter:	19 mm
Inlet from the rear:	Ja
Length:	39 mm
Width:	86 mm
Depth:	86 mm
Tackable:	Nej
Number of inlets:	14
Type of housing feed-through:	Seal membrane
Material:	Plastic
Halogen free:	Ja
Surface protection:	Untreated
Colour:	White
Degree of protection (IP):	IP65

# Produktblad

Surface-mounted junction box, IP65, 86 x 86 mm, white



Cover model:	Blind cover
Transparent cover:	Nej
Cover attachment:	Snapped on
Castable:	Nej
With casting compound:	Nej
Sealable:	Ja
Rated insulation voltage Ui:	500 V
With screening:	Nej
Weatherproof:	Ja
Operating temperature:	-25...60 °C
Explosion-tested version:	Nej